

5M SEIKO SPT510 SOLVENT PRINTER

Print Technology	Drop-On-Demand Piezo Electric (SEIKO/SPT510-35PL)
Print Head	12/8/6/4 Heads (Seiko/spt 510) 6color or 4 color
Print Width	5m width
Resolution	720dpi Max
Speed	1 Pass 153 m2/h
	2 Pass 116m2/h
	3 Pass 78m2/h
	4 Pass 40 m2/h
Locating Mode	Double Servo Driver/Servo Motor
Media Width	5.2m
Color	C M Y K
Ink Type	Special ink for Seiko/Spt510
Ink	Solvent based Pigment Ink, At least tow years outdoor
Ink delivery system	Negative pressure ink supply system, Main ink case 1L/color
Media Handle	Roll to Roll
Media feeding &take-up system	Infra Red Optical Controlling System for Media Feeding &Take-up
Dry system	Pre/Post and Middle heater controlled by PID
Media Type	PVC Vinyl, Flex banner, Carpet Paper, PVC Mesh Fabric, Perforated Vinyl, Cloth Banner Etc.
Motor	Fuji or Panasonic AC Servo Motor
Linear Rail	THK /HLWIN
Height of Print-head	1mm -10mm above media, Adjustable
Print head maintenance facility	Protection trays for auto purge, daily maintenance and print heads over night
Auto-cleaning system	Double functional cleaning System of Pressure purge and Vacuum Suction
Interface	USB2.0
Print Mode	Bidirectional Printing
File Format	TIFF, JPEG, Postscript 3, EPS, PDFRGB/CMYK
RIP Software	Original Maintop/Photoprint Rip software
Working Process	Maintop software, Photoprint software for Windows 98 and Windows XP Etc.
Power Supply	50HZ/60HZ, 220V(±10%)>15A
Filtration Facility	PALL filter + Regular ink filter
Operation Environment	Temperature: 23~29 Degrees ; Humidity: 50%~80%